

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-154083

(43)Date of publication of application : 13.06.1990

(51)Int.Cl.

D06P 5/00

B41M 1/24

(21)Application number : 63-306598

(71)Applicant : TOPPAN PRINTING CO LTD

(22)Date of filing : 02.12.1988

(72)Inventor : MURAKAMI SANJI

(54) METHOD FOR COLORING AND EMBOSSING

(57)Abstract:

PURPOSE: To subject a sheet to coloring and embossing processing without causing fading and disappearance of unevennesses due to washing by superposing a transfer sheet having a formed specific resin layer on a fabric, partially transferring the resin layer and an ink layer to the fabric, simultaneously forming recessed parts and then heat-treating the resultant sheet.

CONSTITUTION: A transfer sheet prepared by forming a resin layer consisting of resin (e.g. polyolefin or polyester) heat bondable to a fabric, such as polyester or nylon, and an ink layer containing a sublimation dye on a releasable sheet is superposed on the fabric and partially hot-pressed to partially transfer the above-mentioned resin layer and ink layer to the fabric and simultaneously form recessed parts. The whole surface is then heat-treated to permeate and apply the dye into the fabric and carry out coloring and embossing processing with a good accuracy. The afore-mentioned method is suitable for processing napped fabrics or thick sheets, etc.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office



(19)

(11) Publication number:

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 63306598

(51) Intl. Cl.: D06P 5/00 B41M 1/24

(22) Application date: 02.12.88

(30) Priority: (43) Date of application publication: 13.06.90 (84) Designated contracting states:	(71) Applicant: TOPPAN PRINTING C (72) Inventor: MURAKAMI SANJI (74) Representative:
---	--

(54) METHOD FOR COLORING AND EMBOSING

(57) Abstract:

PURPOSE: To subject a sheet to coloring and embossing processing without causing fading and disappearance of unevennesses due to washing by superposing a transfer sheet having a formed specific resin layer on a fabric, partially transferring the resin layer and an ink layer to the fabric, simultaneously forming recessed parts and then heat-treating the resultant sheet.

CONSTITUTION: A transfer sheet prepared by forming a resin layer consisting of resin (e.g. polyolefin or polyester) heat bondable to a fabric, such as polyester or nylon, and an ink layer containing a sublimation dye on a releasable sheet is superposed on the fabric and partially hot-pressed to partially transfer the above-mentioned resin layer and ink layer to the fabric

Handwritten notes:
103- 02/12/88
116-19-23
3-110
15-19
103- 02/12/88
42-2000

and simultaneously form recessed parts. The whole surface is then heat-treated to permeate and apply the dye into the fabric and carry out coloring and embossing processing with a good accuracy. The afore-mentioned method is suitable for processing napped fabrics or thick sheets, etc.

COPYRIGHT: (C)1990,JPO&Japio